

# GripKote 300

## DESCRIPTION

GripKote 300 is a multi-purpose waterbased bitumen emulsion that provides a quick and economical method of applying a waterproofing membrane that is non-hazardous, non-toxic and odour free.



## AREAS OF APPLICATION

- Retaining walls
- Protection of metal roofs, gutters and downpipes
- Protection of most timber products, such as fence posts
- Horticulture - to seal pruning cuts and grafts
- Concrete surfaces and rendering

## SURFACE PREPARATION

All surfaces must be clean, dry and free from any loose materials such as paint, oils and rust.

## APPLICATION

Before use, stir contents of GripKote 300 thoroughly. Apply two coats by brush, roller, trowel or high-pressure airless spray gun at approximately 1 square meter per litre per coat. Allow first coat to fully dry before applying 2nd coat. Drying time 4-24 hours depending on drying conditions.

## COVERAGE

Approx 1 square meter per litre per coat depending on surface.

## PRECAUTIONS

Do not apply below 5°C, where hydrostatic pressure exists or when damp conditions may prevent the emulsion from drying out. Affected by oils, solvents and some detergents.

Where GripKote 300 is left exposed to sunlight, it should be painted with an acrylic paint to prevent breakdown caused by UV light. (Allow at least six weeks before painting.)

Maximum thickness of a single coat must not exceed 1mm.

When applied to timber, old surfaces should be sanded down to provide a flat, even surface.

When using GripKote 300 to waterproof retaining walls etc, ensure the membrane is covered with corflute or similar material to prevent piercing of the membrane.

Continued over page.

#### PACKAGING

Available in 1L, 4L and 20L containers.

#### CLEAN UP

Use cold water when wet, mineral turps when material is dry.

#### STORAGE

Do not allow containers to freeze. May be stored for 24 months in a sealed container under cover between 5°C and 40 °C. For long term storage of partly used containers. Level off contents of containers and cover surface with five centimeters of water and replace lid tightly. Before resuing GripKote 300, pour off excess water and stir emulsion thoroughly.



## TECHNICAL DATA SHEET

50 Merrindale Drive  
Croydon South VIC 3136  
P: 1300 ALLCON (255 266)  
E: sales@allcongroup.com.au

[www.allcongroup.com.au](http://www.allcongroup.com.au)

Allcon products are manufactured to the highest quality, and if used in the correct applications and in accordance with all directions, will produce quality and consistent results. However Allcon Group Pty Ltd accepts no responsibility for inappropriate usage or faulty workmanship by the end user.

Product: GripKote 300  
Issue Date: 27 Jan 2022