

TECHNICAL DATA SHEET

- Jointing Systems
- Polythene Builders Film
- Formwork
- Formworking Accessories
- Nails
- Tie Wire
- Loop Ties
- Waterproofing

P: 1300 ALLCON (255 266)
E: sales@allcongroup.com.au

www.allcongroup.com.au

Set-Up Expansion Joint

DESCRIPTION

Set-up expansion joint is a closed cell foam based material with an optional adhesive backing. It is typically used in concrete construction and isolation joints to provide allowance for concrete expansion preventing cracking.



FEATURES

- Available with Adhesive Backing to adhere directly to vertical surfaces
- 10mm tear off strip to allow the application of joint sealants
- Available in various sizes from 50mm to 300mm
- Designed to prevent cracking from expansion pressures
- Easily to cut and install on site
- Readily compressible and recovers well after compression
- Non absorbent and will not rot
- CFC free.

ESTIMATING & SIZES

Expansion joint is 10mm in thickness and available in 25m rolls in the following widths:

- 50mm
- 75mm
- 100mm
- 125mm
- 150mm
- 200mm
- 250mm
- 300mm

Larger sizes and thicknesses are available on request.

APPLICATION INSTRUCTIONS

Ensure substrate is clean and free of dust or debris. Position the expansion joint ensuring that the perforated strip is facing upwards and that the joint is applied flush with the finished level of the concrete.

The standard expansion joint should be held in place using a construction adhesive or concrete nails or a combination of both.

If using the adhesive (Sticky) backed option, remove the paper backing and press firmly on to the surface. This may also require the use of concrete nails to assist with adhesion.

Set-Up products are manufactured to the highest quality, and if used in the correct applications and in accordance with all directions, will produce quality and consistent results. However Allcon Group Pty Ltd accepts no responsibility for inappropriate usage or faulty workmanship by the end user.

Product: Set-Up Expansion Joint
Issue Date: 31 March 2021