

Product information February 2020

## VB3616DA(HGZ)

Rebar Cutter & Bender

36V Rebar Cutter & Bender

Barcode 4966376331772





# Reverse rotation mode for precision angle alignment

4 angle settings from 45° to 180°

**Brushless DC motor** 

#### **Specifications** Rebar material yield strength 460 N/mm<sup>2</sup> (47kg/mm<sup>2</sup>) max Capacity Max rebar diameter 16mm 10mm max 2 Cutting 12mm max 1 16mm max 1 No of Possible Rebars at a time 10mm max 3 Bending 12mm max 2 16mm max 1 Bending Angle 0° to 180° (stepless) No -load speed 0 to 16min<sup>-1</sup> 2.6 sec Cutting Speed Bending 3.8 sec Cutting 170 approx No. of operations per charge Bending 310 approx Fan-cooled DC Brushless Motor Switch Trigger Weight 18.9kg Dimensions (L x W x H) 510 x 230 x 241mm

#### **Selling Points**

Cutting and bending in one unit Excellent cutting and bending performance

#### Features

Reverse rotation mode for precision angle alignment

Controller to prevent interuption of bending/cutting operation

4 angle settings from 45° to 180°

Brushless DC motor

#### **Included Accessories\***

Battery cover

Hex. Bar wrench 4mm

Case

Battery (BSL36A18 x 2) and charger (UC18YSL3) included

### Applications

Cutting of Rebar Bending of Rebar



HiKOKI Power Tools Australia reserves the right to change specifications of parts and accessories of HiKOKI power tools without notice. Product images are for display purposes only. Accessories not included unless otherwise stated. Product information should be confirmed at time of purchase. Errors & Omissions excepted.

HiKOKI 6 YEAR WARRANTY More information about our conditions at www.hikokipowertools.com.au