



## TECHNICAL DATA SHEET

- Coatings
- Curing
- Waterproofing
- Moisture Proofing
- Protection
- Repair Products
- Primers
- Repellent

# BossCure 100

## DESCRIPTION

BossCure 100 is a high solids, water-based PVA curing compound specifically formulated reduce moisture evaporation and improve the curing process of the concrete. The specially selected polymer emulsion will not normally interfere with after trades such as tile adhesives, renders, toppings etc and will naturally break down with exposure to UV light within 6-8 weeks.



## AS3799 CLASSIFICATION

- Class D, Type 1D
- Not compliant with AS3799

## AREAS OF APPLICATION

- For curing all freshly laid concrete either smooth or textured, indoors or outdoors

## FEATURES & BENEFITS

- Economical
- Fast Drying
- Easy Application
- Great Insurance Policy against shrinkage cracking
- Ideal for non critical pavements such as driveways, patios and pathways.

## APPLICATION INSTRUCTIONS

Stir Bosscure 100 thoroughly prior to application.

Apply Bosscure 100 should be applied to the surface of freshly finished concrete once the concrete has hardened sufficiently so as not to be marked by the application process.

Apply

BossCure 100 undiluted at a rate of 1 litre per 5m<sup>2</sup>. Best applied by spray, however, may also be applied by brush, roller or broom.

If after-trades need to be applied it is recommended that a period of 28 days from the date of pouring has elapsed before any after-trades are applied.

Continued over page...

## CLEAN UP

Wash all tools and equipment in clean water immediately after use.

## TYPICAL PROPERTIES

Appearance:	Milky white emulsion
Coverage:	5m <sup>2</sup> per litre
Solids:	Not applicable
Solubility in Water:	Miscible
Flash Point:	Not Applicable
Solvents:	Not Applicable
Shelf Life:	12 Months Maximum
Dry Time:	20mins @ 25°C
Application Temperature:	10°C - 35°C
Application by:	Spray, Brush, Roller or Broom
Packaging:	20L, 205L or 1000L
UN Number:	Not Applicable
Hazchem Code:	Not Applicable
Packaging Group:	Not Applicable
Poison Schedule:	Not Applicable
Dangerous Goods Class:	Not Applicable

## HEALTH & SAFETY

Avoid Contact with skin. Protective gloves and clothing are recommended when mixing or using this product.

Please refer to the full MSDS (Material safety data sheet) for this product, which is available from Allcon on request.

## DISCLAIMER

Boss products are manufactured to the highest quality, and if used in the correct applications and in accordance with all directions, will produce quality and consistent results. However, Allcon Group Pty Ltd accepts no responsibility for inappropriate usage or faulty workmanship by the end user.

Product: BossCure 100

Issue Date: March 2023



## TECHNICAL DATA SHEET

- Coatings
- Curing
- Waterproofing
- Moisture Proofing
- Protection
- Repair Products
- Primers
- Repellent

P: 1300 255 266  
E: [sales@allcongroup.com.au](mailto:sales@allcongroup.com.au)

[www.allcongroup.com.au](http://www.allcongroup.com.au)