

TECHNICAL DATA SHEET

- Coatings
- Curing
- Waterproofing
- Moisture Proofing
- Protection
- Repair Products
- Primers
- Repellent

BossCure 900

DESCRIPTION

BossCure 900 is a bitumen/hydrocarbon blend emulsified in water and is both a curing compound and primer coat for asphalt and bitumen overlays. BossCure 900 satisfies the requirements of AS3799 standard of for curing achieving a water retention of greater than 90%.



AREAS OF APPLICATION

- For curing all freshly laid concrete either smooth or textured, indoors or outdoors
- Also acts as a primer for bitumen overlays, commonly found on bridge decks and in road construction.

FEATURES & BENEFITS

- Complies to AS3799 standard for concrete curing
- Achieves water retention of 90% or greater
- Totally water based with no solvent odour
- Doubles as a primer coat for bitumen and asphalt overlays
- Clean equipment with water

APPLICATION INSTRUCTIONS

Apply BossCure 900 to the surface of freshly finished concrete once concrete has hardened sufficiently not to be marked by the application process. Apply BossCure 900 undiluted at a rate of 1 Litre per 4.5 square meters.

BossCure 900 is best applied by a pump or airless sprayer, however it can also be applied using a brush, roller or broom.

If the concrete surface is required to be trafficable PRIOR to having an overlay placed, then fine sand or fine stone can be placed over the BossCure 900 to increase abrasion resistance of the coating.

Caution: BossCure 900 is NOT a “Tack Coat”.

Continued over page...

CLEAN UP

Wash all tools and equipment in clean water immediately after use.

TYPICAL PROPERTIES

Appearance:	Black free flowing liquid
Coverage:	4.5m ² per litre
Viscosity:	0.22 pascal seconds
Solids:	50% or greater
Solubility in Water:	Soluble
Flash Point:	100°C
Solvents:	Not Applicable
Shelf Life:	6 Months Maximum
Dry Time:	Tack Free: 1 - 3 Hours
	Hard Dry: 4 - 8 Hours
	Trafficable: 24 Hours
Application Temperature:	10°C - 35°C
Application by:	Spray, Brush Roller or Broom
Packaging:	20L, 205L or 1000L
UN Number:	Not Applicable
Hazchem Code:	Not Applicable
Packaging Group:	Not Applicable
Poison Schedule:	5
Dangerous Goods Class:	Not Applicable

HEALTH & SAFETY

Avoid Contact with skin. Protective gloves and clothing are recommended when mixing or using this product.

Please refer to the full MSDS (Material safety data sheet) for this product, which is available from Allcon on request.

DISCLAIMER

Boss products are manufactured to the highest quality, and if used in the correct applications and in accordance with all directions, will produce quality and consistent results. However, Allcon Group Pty Ltd accepts no responsibility for inappropriate usage or faulty workmanship by the end user.

Product: BossCure 900

Issue Date: October 2020



TECHNICAL DATA SHEET

- Coatings
- Curing
- Waterproofing
- Moisture Proofing
- Protection
- Repair Products
- Primers
- Repellent

P: 1300 255 266

E: sales@allcongroup.com.au

www.allcongroup.com.au