

EROSION CONTROL

PRODUCT DATA SHEET

DESCRIPTION

Boss Erosion Control (BEC) is a specialty product developed as a soil stabilisation binder for non-trafficable areas.

BEC is diluted with water and will form a long-term crust on application to open ground areas.

BEC is effective on all material types and will also provide a long-term solution to protect against wind and water erosion

PRODUCT ADVANTAGES:

- Increased surface life and reduced dust levels.
- Easily applied through any watering system, dilutes with water.
- Product can last up to 18 months when applied correctly.
- Maintains natural appearance.
- Improved surface load carrying capacity.
- Improved structural integrity, effective in wet conditions.
- Strong resistance to wind and water erosion.
- Will not wash out of the soil by rain/water.
- Reduction in maintenance costs for untreated surfaces.

DIRECTIONS FOR USE:

BEC is diluted with water and applied by a watering system at a rate of 1:9-1:2 (10-33%) with water depending on application.

Coverage rate for application is recommended at a rate of 1-2m²/L.

Stabilisation trials to determine the desired ratio are recommended.

DILUTION RATE	1:9 Water 1:2 Water
COVERAGE RATE	1-2 m ² /L

Allow Boss Erosion Control (BEC) to dry completely to be fully effective. For best results avoid application to waterlogged or wet clay areas where possible, allow ground surface area to dry out prior to application.

Boss Erosion Control (BEC) is an off-white milky appearance, dye markers can be added as a visual aid for application.

FIRST AID, SAFETY & STORAGE:

Refer to Material Safety Data Sheet

BOSS EROSION CONTROL (BEC) - PDS DEC 2024

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Allcon Group does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.